

A= Brand sticker
 A Accord
 X Automax
 P PMV

B= Shaft
 N Namur VDI/VDE 3845
 D Double D 1/4"

C= Connections (cable entry)
 XV Aluminium Housing 3 x 3/4" NPT
 XM Aluminium Housing 3 x M20 x 1,5

D= Indicator option
 U Standard Ultradome Red/Green
 3 4 window Ultradome
 C 90 deg 3 way Ultradome
 D 180 deg 3 way Ultradome
 E 180 deg 3-way Centre-blocked Ultradome
 F 121 deg Thru/Divert Ultradome
 H Black/Yellow Ultradome
 K Ektar Ultradome (red/green)
 R Reverse Ultradome (red = Open / green = closed)
 W White/Blue Ultradome
 X 180 deg 3-way Ultradome White/Blue

E= Qty of switches
 2 2 switches
 4 4 switches

F= Switch options (qty of switch)

	2x	4x
M1 SPDT Mechanical switches 250VAC 10A		
MG SPDT Mechanical gold plated		
MB DPDT Mechanical - Licon		
P4 SPST Proximity		
PE Sabre SPDT Proximity		
PP Phazer II SPDT Proximity		
PL Phazer II SPDT Proximity with LED		
PT Phazer II BRS SPST Proximity		
PX Phazer II BRS SPST Proximity with LED		
N8 P&F NJ2 V3 N (Namur)		
NP P&F SJ3.5-N (NAMUR)		

G= Certificate
 14 General Purpose
 17 CSA Cl.1, Div.1&2, Grp. C,D
 19 ATEX II 2 G EEx d IIB T4
 24 CSA Cl.1, Div.1&2, Grp. C,D
 25 IECEX II 2 G EEx ia IIC T4-T6, II 2 D Ex tD A21 IP66
 27 FM/CSA IS Cl.1, Div2, Gr.A-D / Cl.2, Div2, Gr.FG
 31 INMETRO Ex certificate

H= Number of coils
 0 Internal single coil

I= Solenoid coil voltage
 0 None
 A 110VAC 50/60Hz 2 Watt
 C 220VAC 50/60 Hz 2 Watt
 F 12VDC 2 Watt
 G 24VDC 2 Watt
 H 12VDC Low power 0,67 Watt
 J 24VDC Low power 0,67 Watt
 K 24VDC Intrinsically safe

J= Spool valve options
 000 None
 3A2 3-way Aluminium -Cv 1,8
 3S2 3-way Stainless steel -Cv 1,8
 3A4 3-way Aluminium -Cv 4,5
 3S4 3-way Stainless steel -Cv 4,5
 4A2 4-way Aluminium -Cv 1,8
 4S2 4-way Stainless steel -Cv 1,8
 4A4 4-way Aluminium -Cv 4,5
 4S4 4-way Stainless steel -Cv 4,5

K= Coating options
 P Powder coating, black (standard)
 E White epoxy coating

L= Spool valve exhaust mufflers
 0 None
 R Thermoplastic rain caps (standard)
 B Sintered Bronze exhaust mufflers
 S Stainless steel exhaust mufflers

M= Override options
 N None (standard)
 M Momentary Manual override
 L Locking Manual override

N= Other options
 0 None
 1 Silicone free
 E Wiedmuller (EU style)
 P High temp Phenolic
 L Low temperature spool -40 deg C/F

Example

A	B	C	D	E	F	-	G	-	H	I	J	K	L	M	N
AX	N	XV	U	2	M1	-	19	-	0	A	3A2	P	R	N	0